



Specifications Multipack 5x Noxion LED Panel Delta Value V5 Backlit 28W 3920lm 830/840 CCT | 60x60cm - < 22 - Philips Driver

[View Product](#)

## General Information

|                      |                                                                                                 |
|----------------------|-------------------------------------------------------------------------------------------------|
| SKU                  | 259058                                                                                          |
| EAN                  | 8719157079488                                                                                   |
| Manufacturer Code    | 8719157079488                                                                                   |
| Brand                | Noxion                                                                                          |
| Manufacturer Name    | Multipack 5x Noxion LED Panel Delta Value V5.1 28W 3920lm 2CCT 600*600 (Philips Driver) Backlit |
| Budgetlight warranty | 6 Years                                                                                         |
| Average Lifetime (h) | 90000                                                                                           |
| Product Serie        | Delta Value                                                                                     |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 4x18                             |
| Wattage                     | 28W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light Colour Options        | CCT                              |

|                        |                   |
|------------------------|-------------------|
| Luminous Flux (Lumen)  | 3920lm            |
| Lumen per watt         | 140               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection     | Push Terminal     |
| Afwerking Reflector    | Frosted           |
| Powerfactor            | >0.90             |
| Type product           | LED Panel         |

## Fixture Information

|                       |                          |
|-----------------------|--------------------------|
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 22 - For general areas |
| Optische Afdekking    | PS (Polystyrene)         |
| Bedrijfstemperatuur   | -20 to +40               |
| Emergency Lighting    | No                       |
| Colour of the Fixture | White                    |
| Housing               | Steel                    |

## Dimensions

|                       |         |
|-----------------------|---------|
| Afmetingen LED Paneel | 60x60cm |
| Length (mm)           | 595     |
| Width (mm)            | 595     |
| Height (mm)           | 32      |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor



**Easy** return process

No Sensor



Long-life **LED solutions**